

Quadruped Unmanned Ground Vehicle

Type	Quadruped
Stowed Dimensions (LxWxH)*	51" × 20" × 16"
Weight (with batteries)	106.5 lb
Cameras	• High-definition integral cameras (front drive camera, omnidirectional camera tower) • 5 pairs of stereo cameras providing 360° of visibility • Enhanced LED illumination
Battery	• One integral battery • 60-minute charge time • 90-minute operational run-time
Max Speed	3.58 MPH
Environmental	• IP54 rating • Environmentally sealed • Temperature range -4°F to 122°F
Arm/Gripper*	• 6 degrees of freedom arm and gripper • 16.3 lb max lift
Transmission Range (LOS)*	2724 ft
Warranty	1-year limited
Technical Support	Unlimited technical support
Front Mounted Manipulation Arm	Degrees of freedom: 6 + gripper Length at full extension: 984–985 mm Weight/Mass: 8 kg (including gripper) Lift capacity: Up to 11 kg Continuous lift capacity (at 0.5 m extension): 5 kg Drag capacity (on carpet): Up to 25 kg Operating temperature: -20°C to 45°C Ingress protection: IP54 (water and dust resistant)
30X Zoom PTZ Inspection Camera + Thermal	30x Optical Zoom PTZ Radiometric Thermal Imaging 360° Panoramic View Industrial Audio & Lighting
Extended MPU5 Radio Kit with GXP	Multi-Radio Setup Radio Extended Range Radio Pkg Set of Two
Training for Law Enforcement Officers	